## NSN 5355-01-078-3497



Knob - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5355-01-078-3497 **Inside Diameter:** Between 0.080 inches and 0.082 inches **Counterbore Diameter:** 0.370 inches **Counterbore Depth:** Between 0.011 inches and 0.041 inches **Setscrew Hole Quantity:** 2 **Distance From Hole Center To Knob/skirt Base:** 0.158 inches **Overall Depth:** 0.406 inches **Gripping Surface Condition:** Smooth **Shaft Accommodation Style:** Counterbored **Outside Diameter:** Between 0.530 inches and 0.570 inches **Reference Marking:** Dot **Attachment Method:** Setscrews **Overall Thickness:** Between 0.480 inches and 0.540 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 40 screw hole Thread Size: 0.112 inches screw hole **Special Features:** Slip clutch has 6 detents, with torque pounds per square inch of 1.0 min 1.5 max Gray, federal standard 595, 36231 **Style Designator:** Round **Thread Series Designator:** Unc screw hole Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5355-01-078-3497

Knob - Page 2 of 2



Demi			

No

Fiig:

A530m0