

View Online at <https://aerobasegroup.com/nsn/5355-01-079-1964>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.310 inches

**Overall Depth:**

0.610 inches

**Width:**

0.700 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Flatted one side

**Length:**

1.000 inches

**Skirt Style:**

Flared

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.224 inches

**Overall Thickness:**

0.690 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.000 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Transilluminated, shaft accommodation hole counterbore, 0.380 in. Dia, 0.160 in. Depth, top counterbore 0.530 in. Dia, 0.080 in. Depth

**Style Designator:**

Bar with single pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0