

View Online at <https://aerobasegroup.com/nsn/5355-01-082-6655>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.158 inches

Overall Depth:

0.405 inches

Width:

Between 0.490 inches and 0.530 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Length:

Between 0.730 inches and 0.780 inches

Reference Marking:

Line

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.227 inches

Overall Thickness:

Between 0.480 inches and 0.540 inches

End Application:

Ticonderoga class cg (47), aircraft, eagle f-15helicopter, super jolly h-53, wasp class lhd, arleigh burke class ddg, helicopter, hh-53h pave low, an/tsw-7a air traffic control center, iff aims mk xii, nimitz class cvn

Screw Drive Type:

Hexagon socket

Thread Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Pointer Design:

Nondetachable

Special Features:

Shaft accommodation hole counterbored 0.420 in. Min dia, 0.026 in. Min depth

Color:

Black

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0