## NSN 5355-01-085-4562

Knob - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5355-01-085-4562

#### **Inside Diameter:**

Between 0.254 inches and 0.262 inches

#### **Counterbore Diameter:**

0.485 inches

## Counterbore Depth:

0.188 inches

## Setscrew Hole Quantity:

2

#### Distance From Hole Center To Knob/skirt Base:

0.369 inches

**Overall Depth:** 

0.568 inches

**Gripping Surface Condition:** 

Grip aid

#### Shaft Accommodation Style:

Counterbored

#### **Outside Diameter:**

Between 0.690 inches and 0.730 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

#### **Overall Thickness:**

Between 1.025 inches and 1.125 inches

Screw Drive Type:

Hexagon socket

#### Thready Qty Per Inch (tpi):

40 screw hole

### Thread Size:

0.112 inches screw hole

#### Skirt Outside Diameter:

0.680 inches

#### Skirt Design:

Nondetachable

#### **Special Features:**

Tactile form, tune; knob contains bushing, part number rb100, fscm 94144; additional color: orange

Color:

Black

#### Material:

Aluminum alloy and plastic and stainless steel

#### Style Designator:

Round with fluted foils

# NSN 5355-01-085-4562

Knob - Page 2 of 2

## **Thread Series Designator:**

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A530m0

