

View Online at <https://aerobasegroup.com/nsn/5355-01-085-4925>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

Between 0.665 inches and 0.715 inches

Width:

Between 1.125 inches and 1.175 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Skirt Style:

Stepped

Reference Marking:

Line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.665 inches and 0.715 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.680 inches

Skirt Design:

Nondetachable

Special Features:

Concentric

Color:

Black

Style Designator:

Skirted/round with double fin lever

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0