

View Online at <https://aerobasegroup.com/nsn/5355-01-087-1994>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.485 inches

**Counterbore Depth:**

0.188 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.369 inches

**Overall Depth:**

0.568 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Skirt Style:**

Stepped

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.025 inches and 1.125 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

0.680 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Tactile form 1-intensity; knob contains bushing, part number rb100, fscm 94144

**Style Designator:**

Round with triangular face

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0