## NSN 5355-01-087-1996

Knob - Page 1 of 2

Material:

Aluminum alloy and plastic and stainless steel



View Online at https://aerobasegroup.com/nsn/5355-01-087-1996 **Inside Diameter:** Between 0.252 inches and 0.254 inches **Counterbore Diameter:** 0.485 inches **Counterbore Depth:** 0.188 inches **Setscrew Hole Quantity: Distance From Hole Center To Knob/skirt Base:** 0.369 inches **Overall Depth:** 0.568 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Counterbored **Outside Diameter:** Between 0.690 inches and 0.730 inches Length: Between 0.690 inches and 0.730 inches **Skirt Style:** Stepped **Attachment Method:** Setscrews **Overall Thickness:** Between 1.025 inches and 1.125 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 40 screw hole **Thread Size:** 0.112 inches screw hole **Skirt Outside Diameter:** 0.680 inches **Skirt Design:** Nondetachable **Special Features:** Knob contains bushing, part number rb100, fscm 94144; additional color: violet Color: Black

## NSN 5355-01-087-1996

Knob - Page 2 of 2



| Style | Des | siar | ato  | r- |
|-------|-----|------|------|----|
| Otylo |     | , gi | iato |    |

Round with cross face

**Thread Series Designator:** 

Unc screw hole

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530m0