

View Online at <https://aerobasegroup.com/nsn/5355-01-088-7350>

**Inside Diameter:**

Between 0.158 inches and 0.160 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.360 inches

**Overall Depth:**

0.605 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Round

**Outside Diameter:**

Between 0.901 inches and 0.941 inches

**Skirt Style:**

Flared

**Reference Marking:**

Dot

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.855 inches and 0.915 inches

**Screw Drive Type:**

Slot

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

Between 1.045 inches and 1.075 inches

**Skirt Design:**

Nondetachable

**Special Features:**

With 0.156 in. Diameter flutes 4 places w/white dot 0.070 in. Min and 0.110 in. Max; with marking on knob using matte white matl; white on surface of inner ring next to flutes; slip clutch mechanism built into knob w/4 to 6 detent positions; access hole in body of knob

**Color:**

Gray, federal standard 595, 36231

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0