## NSN 5355-01-088-7350



Knob - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5355-01-088-7350 **Inside Diameter:** Between 0.158 inches and 0.160 inches **Setscrew Hole Quantity:** 2 Distance From Hole Center To Knob/skirt Base: 0.360 inches **Overall Depth:** 0.605 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Round **Outside Diameter:** Between 0.901 inches and 0.941 inches **Skirt Style:** Flared **Reference Marking:** Dot **Attachment Method:** Setscrews **Overall Thickness:** Between 0.855 inches and 0.915 inches **Screw Drive Type:** Slot Thready Qty Per Inch (tpi): 40 screw hole **Thread Size:** 0.112 inches screw hole **Skirt Outside Diameter:** Between 1.045 inches and 1.075 inches **Skirt Design:** Nondetachable **Special Features:** With 0.156 in. Diameter flutes 4 places w/white dot 0.070 in. Min and 0.110 in. Max; with marking on knob using matte white matl; white on surface of inner ring next to flutes; slip clutch mechanism built into knob w/4 to 6 detent positions; access hole in body of knob Color: Gray, federal standard 595, 36231 **Style Designator:** Round

N/a

**Thread Series Designator:** 

Unc screw hole Shelf Life:

## NSN 5355-01-088-7350

Knob - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A530m0