

View Online at <https://aerobasegroup.com/nsn/5355-01-089-6086>

**Inside Diameter:**

Between 0.158 inches and 0.160 inches

**Counterbore Diameter:**

0.370 inches

**Counterbore Depth:**

Between 0.080 inches and 0.110 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.400 inches

**Overall Depth:**

0.587 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.530 inches and 0.570 inches

**Skirt Style:**

Flared

**Reference Marking:**

Two dots

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.650 inches and 0.710 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

Between 0.685 inches and 0.715 inches

**Skirt Design:**

Nondetachable

**Special Features:**

One dot is on top of knob, one dot is on skirt, dots have a matte luster, slip clutch has 6 detented positions in 360 degrees, 1.0 min, 1.5 maximum psi

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0