

View Online at <https://aerobasegroup.com/nsn/5355-01-089-6086>

Inside Diameter:

Between 0.158 inches and 0.160 inches

Counterbore Diameter:

0.370 inches

Counterbore Depth:

Between 0.080 inches and 0.110 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.400 inches

Overall Depth:

0.587 inches

Gripping Surface Condition:

Smooth

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.530 inches and 0.570 inches

Skirt Style:

Flared

Reference Marking:

Two dots

Attachment Method:

Setscrews

Overall Thickness:

Between 0.650 inches and 0.710 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

Between 0.685 inches and 0.715 inches

Skirt Design:

Nondetachable

Special Features:

One dot is on top of knob, one dot is on skirt, dots have a matte luster, slip clutch has 6 detented positions in 360 degrees, 1.0 min, 1.5 maximum psi

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0