

View Online at <https://aerobasegroup.com/nsn/5355-01-092-5052>

**Inside Diameter:**

Between 0.250 inches and 0.255 inches

**Setscrew Hole Quantity:**

1

**Distance From Hole Center To Knob/skirt Base:**

Between 0.340 inches and 0.360 inches

**Overall Depth:**

Between 0.720 inches and 0.740 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

Between 1.470 inches and 1.530 inches

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.220 inches and 0.225 inches

**Overall Thickness:**

Between 0.770 inches and 0.830 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Pointer Design:**

Nondetachable

**Special Features:**

Illumination through top of knob, shaft accommodation hole counterbored, 0.470 in. Min dia, 0.530 in. Maximum dia, 0.235 in. Min depth, 0.255 in. Maximum depth

**Style Designator:**

Round with single pointed bar face

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0