

View Online at <https://aerobasegroup.com/nsn/5355-01-094-2926>

**Unable To Decode:**

Unable to decode and unable to decode

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.440 inches and 0.500 inches

**Overall Depth:**

Between 0.620 inches and 0.835 inches

**Shaft Accommodation Style (non-core):**

Err-090

**Outside Diameter:**

Between 0.990 inches and 1.010 inches

**Attachment Method:**

Setscrews

**Knob Portion Diameter:**

Between 0.490 inches and 0.510 inches

**Scale Direction And Range:**

1 to 10 clockwise first scale

**Scale Division Quantity:**

9 second scale

**Drive Ratio:**

1.0 single

**Drive Type:**

Direct and gear

**Scale Type:**

Linear all scales

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.138 inches screw hole

**Positioning Mechanism Type:**

Knob dual

**Special Features:**

Knob and dials are black lustreless, fed-std 595, no. 37038, markings and numbers are white lustreless, fed-std 595, no. 37875, anti-rotation washer and mounting nut furnished with dial, knob is fluted; additional attachment method: center hole; knob material: plastic; setscrew material: stainless steel; cover material: aluminum alloy 5052; cover surface treatment: anodized

**Height:**

Between 0.880 inches and 0.940 inches

**Material:**

Plastic dial

**Material Specification:**

Err-070

**Surface Treatment Specification:**

Err-070

**Style Designator:**

Round w/knob

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530p0