

View Online at <https://aerobasegroup.com/nsn/5355-01-094-2926>

Unable To Decode:

Unable to decode and unable to decode

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.440 inches and 0.500 inches

Overall Depth:

Between 0.620 inches and 0.835 inches

Shaft Accommodation Style (non-core):

Err-090

Outside Diameter:

Between 0.990 inches and 1.010 inches

Attachment Method:

Setscrews

Knob Portion Diameter:

Between 0.490 inches and 0.510 inches

Scale Direction And Range:

1 to 10 clockwise first scale

Scale Division Quantity:

9 second scale

Drive Ratio:

1.0 single

Drive Type:

Direct and gear

Scale Type:

Linear all scales

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.138 inches screw hole

Positioning Mechanism Type:

Knob dual

Special Features:

Knob and dials are black lustreless, fed-std 595, no. 37038, markings and numbers are white lustreless, fed-std 595, no. 37875, anti-rotation washer and mounting nut furnished with dial, knob is fluted; additional attachment method: center hole; knob material: plastic; setscrew material: stainless steel; cover material: aluminum alloy 5052; cover surface treatment: anodized

Height:

Between 0.880 inches and 0.940 inches

Material:

Plastic dial

Material Specification:

Err-070

Surface Treatment Specification:

Err-070

Style Designator:

Round w/knob

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530p0