

View Online at <https://aerobasegroup.com/nsn/5355-01-102-1918>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

Between 0.790 inches and 0.840 inches

Width:

Between 0.695 inches and 0.725 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Length:

Between 0.945 inches and 0.975 inches

Skirt Style:

Flared

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.224 inches

Overall Thickness:

Between 0.790 inches and 0.840 inches

End Application:

W/s: support equipment, t-38 aircraft; aircraft, starlifter c-141; aircraft, hercules c-130; aircraft, stratolifter c-135; support equipment, t-37 aircraft; aircraft, galaxy c-5

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

Between 0.970 inches and 1.030 inches

Skirt Design:

Nondetachable

Special Features:

Non-illuminated, shaft accommodation hole counterbore 0.485 in. Min dia, 0.188 in. Min depth

Color:

Gray

Style Designator:

Round with bar lever

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0