

View Online at <https://aerobasegroup.com/nsn/5355-01-114-5234>

**Inside Diameter:**

Between 0.127 inches and 0.129 inches

**Counterbore Diameter:**

0.485 inches

**Counterbore Depth:**

0.026 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.203 inches

**Overall Depth:**

0.405 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.815 inches and 0.895 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Special Features:**

0.562 in. Radius indentation down the side of the knob, tactile form-intensity; 0.610 in. Min dia, 0.650 in. Maximum dia; 0.320 in. Min thickness, 0.370 in. Maximum thickness; concentric

**Style Designator:**

Round with triangular face

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0