

View Online at <https://aerobasegroup.com/nsn/5355-01-147-9818>

**Inside Diameter:**

Between 0.252 inches and 0.253 inches

**Counterbore Diameter:**

0.750 inches

**Counterbore Depth:**

0.187 inches

**Setscrew Hole Quantity:**

1

**Distance From Hole Center To Knob/skirt Base:**

Between 0.401 inches and 0.411 inches

**Overall Depth:**

Between 0.610 inches and 0.640 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

0.750 inches

**Skirt Style:**

Flared

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Overall Thickness:**

0.718 inches

**Material Transparency:**

Opaque

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

0.875 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Material is temper t6, temper t651, gloss arrow

**Material:**

Aluminum alloy 6061

**Style Designator:**

Crown

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0