

View Online at <https://aerobasegroup.com/nsn/5355-01-150-9798>

Inside Diameter:

Between 0.252 inches and 0.253 inches

Counterbore Diameter:

0.750 inches

Counterbore Depth:

0.218 inches

Setscrew Hole Quantity:

1

Distance From Hole Center To Knob/skirt Base:

Between 0.401 inches and 0.411 inches

Overall Depth:

Between 0.610 inches and 0.640 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

1.000 inches

Skirt Style:

Flared

Reference Marking:

Arrow

Attachment Method:

Setscrews

Overall Thickness:

0.812 inches

Material Transparency:

Opaque

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.187 inches

Skirt Design:

Nondetachable

Special Features:

Material is temper t6, temper t651, gloss arrow federal standard 595, no. 17875

Material:

Aluminum alloy 6061

Style Designator:

Crown

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0