

View Online at <https://aerobasegroup.com/nsn/5355-01-165-3412>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.325 inches

Overall Depth:

0.560 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.490 inches and 0.530 inches

Skirt Style:

Ring

Reference Marking:

Dot

Attachment Method:

Setscrews

Inside Width:

Between 0.107 inches and 0.112 inches

Overall Thickness:

Between 0.625 inches and 0.685 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.460 inches

Skirt Design:

Nondetachable

Special Features:

Dot is phosphorescent, shaft accommodation hole counterbore 0.300 in. Min dia, 0.177 in. Min depth

Color:

Gray, federal standard 595, 36231

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0