

View Online at <https://aerobasegroup.com/nsn/5355-01-177-9797>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.325 inches

**Overall Depth:**

0.568 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

Between 0.490 inches and 0.530 inches

**Skirt Style:**

Flared

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.227 inches

**Overall Thickness:**

Between 0.625 inches and 0.685 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

1.150 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbored 0.485 in. Min diameter and 0.188 in. Min depth

**Color:**

Black

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Specification Data:**

96906-ms91528 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0