

View Online at <https://aerobasegroup.com/nsn/5355-01-187-2643>

Inside Diameter:

Between 0.118 inches and 0.120 inches

Counterbore Diameter:

Between 0.436 inches and 0.437 inches

Counterbore Depth:

Between 0.410 inches and 0.420 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.520 inches and 0.530 inches

Overall Depth:

Between 0.683 inches and 0.693 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.620 inches and 0.640 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.683 inches and 0.693 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket or slot

Thready Qty Per Inch (tpi):

56 screw hole

Thread Size:

0.086 inches screw hole

Thread Tolerance Class:

2b internal screw hole

Special Features:

Finish: chemical film per mil-c-5541, class 1a

Material:

Aluminum alloy 2024

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0