

View Online at <https://aerobasegroup.com/nsn/5355-01-199-7864>

Inside Diameter:

Between 0.156 inches and 0.158 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Flared

Attachment Method:

Setscrews

Overall Thickness:

Between 0.752 inches and 0.812 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.150 inches

Criticality Code Justification:

Zzzy

Skirt Design:

Nondetachable

Special Features:

Special quality control testing; test data document: 81349-mil-p-23199

Color:

Black

Material:

Aluminum alloy and plastic polycarbonate and stainless steel

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from mercury contamination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530m0