

View Online at <https://aerobasegroup.com/nsn/5355-01-218-9897>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.325 inches

Overall Depth:

Between 0.625 inches and 0.685 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.490 inches and 0.530 inches

Skirt Style:

Flared

Reference Marking:

Slot

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.227 inches

Overall Thickness:

Between 0.625 inches and 0.685 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.900 inches

Skirt Design:

Nondetachable

Special Features:

Counterbore at shaft hole 0.325 in. Maximum diameter and 0.177 in. Dp

Color:

Black, lusterless

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0