## NSN 5355-01-219-4220

Between 3.20 millimeters and 3.30 millimeters

Knob - Page 1 of 2

**Counterbore Diameter:** 

**Counterbore Depth:** 

**Setscrew Hole Quantity:** 

**Inside Diameter:** 

7.0 millimeters

2.5 millimeters



View Online at https://aerobasegroup.com/nsn/5355-01-219-4220

I .
Distance From Hole Center To Knob/skirt Base:
6.0 millimeters
Overall Depth:
11.0 millimeters
Gripping Surface Condition:
Grip aid
Shaft Accommodation Style:
Counterbored
Outside Diameter:
10.0 millimeters
Skirt Style:
Flared
Reference Marking:
Dot
Attachment Method:
Setscrews
Overall Thickness:
13.0 millimeters
Screw Drive Type:
Hexagon socket
Thread Size:
3.0 millimeters screw hole
Skirt Outside Diameter:
12.0 millimeters
Skirt Design:
Nondetachable
Thread Tolerance Class:
6h internal screw hole
Special Features:
Thread pitch in millimeters: 0.50
Color:
Gray and white
Material:
Plastic abs and stainless steel

## NSN 5355-01-219-4220

Knob - Page 2 of 2



Style	Designator:

Crown

**Thread Series Designator:** 

Iso m screw hole

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530m0