NSN 5355-01-224-7406

Control Dial - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5355-01-224-7406

| Setscrew Hole Quantity: |
|---|
| 2 |
| Shaft Accommodation Style (non-core): |
| Err-090 |
| Outside Diameter: |
| 3.000 inches |
| Reference Marking: |
| 1 through 4 |
| Surface Luster: |
| Lusterless |
| Attachment Method: |
| Setscrews |
| Knob Portion Diameter: |
| 1.750 inches |
| Scale Direction And Range: |
| .01 to 5.0 counterclockwise single scale |
| Scale Division Quantity: |
| 24 single scale |
| End Application: |
| 6525-01-159-3009, field radiographic/fluoroscopic x-ray systems; model dxd 350 ii |
| Material Transparency: |
| Clear |
| Drive Type: |
| Direct |
| Scale Type: |
| Linear single scale |
| Screw Drive Type: |
| Hexagon socket |
| Thready Qty Per Inch (tpi): |
| 32 screw hole |
| Thread Size: |
| 0.164 inches screw hole |
| Positioning Mechanism Type: |
| Knob |
| Special Features: |
| Cap material: aluminum; knob material: plastic; cap surface treatment: anodized |
| Height: |
| 0.880 inches |
| Material: |
| Plastic acrylic dial |
| Unpackaged Unit Weight: |

0.046 ounces

NSN 5355-01-224-7406

Control Dial - Page 2 of 2



| to | r: |
|----|----|
| | to |

Round w/knob

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530p0