

View Online at <https://aerobasegroup.com/nsn/5355-01-234-3159>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Flared

Reference Marking:

Arrow

Attachment Method:

Setscrews

Overall Thickness:

Between 1.025 inches and 1.125 inches

Material Transparency:

Clear

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.150 inches

Skirt Design:

Nondetachable

Color:

Gray, federal standard 595, 36231

Material:

Plastic

Style Designator:

Round with arched bar

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0