

View Online at <https://aerobasegroup.com/nsn/5355-01-284-5275>

Inside Diameter:

Between 0.127 inches and 0.132 inches

Counterbore Diameter:

Between 0.390 inches and 0.397 inches

Counterbore Depth:

Between 0.310 inches and 0.330 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.453 inches and 0.490 inches

Overall Depth:

Between 0.650 inches and 0.660 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.484 inches and 0.516 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.734 inches and 0.766 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 socket internal

Thread Size:

0.112 inches socket internal

Pointer Design:

Nondetachable

Special Features:

Pointer mark per mil-std-454; requirement 67 as necessary to enhance cutout; knob color number 37038 per fed-std-595; surface finish is diamond knurl 128 std. Pitch class 1; setscrew sockets are 120 deg. Apart with the first 43.0-47.0 deg. Left of pointer

Color:

Black

Material:

Aluminum alloy 6061

Thread Series Designator:

Unc socket internal

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0