

View Online at <https://aerobasegroup.com/nsn/5355-01-364-2858>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.280 inches and 0.340 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

Between 0.670 inches and 0.730 inches

**Skirt Style:**

Flared

**Reference Marking:**

Indicator line

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.660 inches and 0.720 inches

**End Application:**

Aircraft, airlifter c-17a aircraft 88277

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 setscrew

**Thread Size:**

0.164 inches setscrew

**Skirt Outside Diameter:**

Between 0.097 inches and 1.030 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Thread Tolerance Class:**

3a external setscrew

**Product Name:**

Knob-plastics bar pointer

**Special Features:**

Item contains a 0.385 outside diameter brass insert located .16 from the base of the knob; knob material is per mil-k-25049; indicia is white no 37875per fed-std-595 surrounded by black border color no 37038 per fed-sted-595; knob is jused for general applications

**Color:**

Gray, federal standard 595, 36231

**Material:**

Plastic

**Style Designator:**

Round

**Thread Series Designator:**

Unc setscrew

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0