

View Online at <https://aerobasegroup.com/nsn/5355-01-364-2858>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.280 inches and 0.340 inches

Gripping Surface Condition:

Smooth

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.670 inches and 0.730 inches

Skirt Style:

Flared

Reference Marking:

Indicator line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.660 inches and 0.720 inches

End Application:

Aircraft, airlifter c-17a aircraft 88277

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 setscrew

Thread Size:

0.164 inches setscrew

Skirt Outside Diameter:

Between 0.097 inches and 1.030 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Thread Tolerance Class:

3a external setscrew

Product Name:

Knob-plastics bar pointer

Special Features:

Item contains a 0.385 outside diameter brass insert located .16 from the base of the knob; knob material is per mil-k-25049; indicia is white no 37875per fed-std-595 surrounded by black border color no 37038 per fed-sted-595; knob is jused for general applications

Color:

Gray, federal standard 595, 36231

Material:

Plastic

Style Designator:

Round

Thread Series Designator:

Unc setscrew

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0