

View Online at <https://aerobasegroup.com/nsn/5355-01-433-2755>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.260 inches

**Overall Depth:**

0.520 inches

**Width:**

Between 0.890 inches and 0.930 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Length:**

Between 1.325 inches and 1.375 inches

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.227 inches

**Overall Thickness:**

Between 0.760 inches and 0.820 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Pointer Design:**

Nondetachable

**Special Features:**

Color is federal standard 595, no. 37038, shaft accommodation hole counterbore, 0.640 in. Min da, 0.114 in. Min depth.

**Color:**

Black

**Style Designator:**

Pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0