

View Online at <https://aerobasegroup.com/nsn/5355-01-524-9681>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

Between 0.375 inches and 0.395 inches

**Counterbore Depth:**

Between 0.130 inches and 0.170 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.310 inches

**Overall Depth:**

Between 0.660 inches and 0.700 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.860 inches and 0.900 inches

**Skirt Style:**

Straight

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.730 inches and 0.770 inches

**End Application:**

F/a-22 raptor

**Material Transparency:**

Clear

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 setscrew

**Thread Size:**

0.164 inches setscrew

**Skirt Outside Diameter:**

Between 0.860 inches and 0.900 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Product Name:**

Knob

**Special Features:**

Material thermoplastic molding compound

**Color:**

Gray

**Material:**

Plastic

**Style Designator:**

Round with arched bar

**Thread Series Designator:**

Unc setscrew

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0