

View Online at <https://aerobasegroup.com/nsn/5355-01-524-9681>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

Between 0.375 inches and 0.395 inches

Counterbore Depth:

Between 0.130 inches and 0.170 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.310 inches

Overall Depth:

Between 0.660 inches and 0.700 inches

Gripping Surface Condition:

Smooth

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.860 inches and 0.900 inches

Skirt Style:

Straight

Attachment Method:

Setscrews

Overall Thickness:

Between 0.730 inches and 0.770 inches

End Application:

F/a-22 raptor

Material Transparency:

Clear

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 setscrew

Thread Size:

0.164 inches setscrew

Skirt Outside Diameter:

Between 0.860 inches and 0.900 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Product Name:

Knob

Special Features:

Material thermoplastic molding compound

Color:

Gray

Material:

Plastic

Style Designator:

Round with arched bar

Thread Series Designator:

Unc setscrew

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530m0