

View Online at <https://aerobasegroup.com/nsn/5355-01-528-8765>

Inside Diameter:

Between 0.118 inches and 0.138 inches

Counterbore Diameter:

Between 0.240 inches and 0.260 inches

Counterbore Depth:

Between 0.140 inches and 0.180 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.235 inches and 0.255 inches

Unthreaded Stud Style:

Flatted, one side

Overall Depth:

Between 0.540 inches and 0.580 inches

Fluted Foil Quantity:

8

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.730 inches and 0.770 inches

Attachment Method:

Setscrews and shaft

Outside Width:

Between 0.107 inches and 0.109 inches

Overall Thickness:

Between 0.640 inches and 0.680 inches

End Application:

C-17a acft

Stud Diameter:

Between 0.127 inches and 0.129 inches

Material Transparency:

Clear

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 setscrew

Thread Size:

0.112 inches setscrew

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Product Name:

Knob

Special Features:

Setscrew is ms51021-103

Color:

Gray, federal standard 595, 36231

Material:

Plastic

Style Designator:

Round fluted

Thread Series Designator:

Unc setscrew

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0