

View Online at <https://aerobasegroup.com/nsn/5355-01-528-8765>

**Inside Diameter:**

Between 0.118 inches and 0.138 inches

**Counterbore Diameter:**

Between 0.240 inches and 0.260 inches

**Counterbore Depth:**

Between 0.140 inches and 0.180 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.235 inches and 0.255 inches

**Unthreaded Stud Style:**

Flatted, one side

**Overall Depth:**

Between 0.540 inches and 0.580 inches

**Fluted Foil Quantity:**

8

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.730 inches and 0.770 inches

**Attachment Method:**

Setscrews and shaft

**Outside Width:**

Between 0.107 inches and 0.109 inches

**Overall Thickness:**

Between 0.640 inches and 0.680 inches

**End Application:**

C-17a acft

**Stud Diameter:**

Between 0.127 inches and 0.129 inches

**Material Transparency:**

Clear

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 setscrew

**Thread Size:**

0.112 inches setscrew

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Product Name:**

Knob

**Special Features:**

Setscrew is ms51021-103

**Color:**

Gray, federal standard 595, 36231

**Material:**

Plastic

**Style Designator:**

Round fluted

**Thread Series Designator:**

Unc setscrew

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0