

View Online at <https://aerobasegroup.com/nsn/5355-01-534-6090>

Shank Length:

Between 0.100 inches and 0.140 inches

Counterbore Diameter:

Between 0.360 inches and 0.400 inches

Counterbore Depth:

Between 0.140 inches and 0.180 inches

Shank Diameter:

Between 0.860 inches and 0.900 inches

Shank Style:

Straight

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.290 inches and 0.330 inches

Overall Depth:

Between 0.600 inches and 0.640 inches

Gripping Surface Condition:

Smooth

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.860 inches and 0.900 inches

Skirt Style:

Straight

Reference Marking:

Indicator line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.730 inches and 0.770 inches

End Application:

A/f-22 raptor

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

Between 0.860 inches and 0.900 inches

Skirt Design:

Nondetachable

Special Features:

Mod s/a ms21385-04ggw

Style Designator:

Square or rectangular with bar face

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0