## NSN 5360-00-116-1854

Extension Helical Spring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5360-00-116-1854

Inside Diameter: 0.160 inches Opening Width: 0.031 inches both ends End Style: Machined half loop both ends Spring Free Length: 0.927 inches Coll Quantity: 26 Dosign Type: Coll Quantity: 28 Dosign Type: Colsed Load Rating: 1.30 pounds Coll Heitx Direction: Right-hand Spring Deflection Rate: 3.200 pounds per inch Spring Tree Outside Diameter: 0.212 inches Hook Radius: 0.212 inches Hook Radius: 0.212 inches Spring Length Under Load: 1.343 inches Spring Length Under Load: 1.343 inches Steel St	
Opening Width:0.031 inches both endsEnd Style:Machined half loop both endsSpring Free Length:0.927 inchesColl Quantity:26Design Type:ClosedLoad Rating:1.50 poundsColl Helix Direction:Right-handSpring Deflection Rate:3.200 pounds per inchSpring Tree Outside Diameter:0.421 inchesHook Radius:1.343 inchesSpring Tree Dutside Diameter:1.343 inchesSpring Tree Dispinator:1.343 inchesSpring Tree Dispinator:1.343 inchesSpring Tree Dispinator:2.314Spring Tree Dispinator:2.315Spring Tree Dispinator:3.316Spring Tree Dispinator:3.3173.318Spring Tree Dispinator:3.3183.3193.310 <th>Inside Diameter:</th>	Inside Diameter:
0.031 inches both endsEnd Style:Machined half loop both endsSpring Free Length:0.927 inchesCoil Quantity:28Design Type:ClosedLoad Rating:1.50 pondsColl Heilx Direction:Right-handSpring Deflection Rate:3.200 pounds per inchSpring Free Outside Diameter:0.212 inchesHock Radius:0.427 inchesJourd JonesSpring Free Outside Diameter:0.313 inchesSpring Tree Treatment:1.343 inchesStellSuffer CollStellSuffer CollStellSuffer CollSuffer Coll	0.160 inches
End Style:         Machined half loop both ends         Spring Free Length:         0.927 inches         Coll Quantity:         28         Design Type:         Closed         Load Rating:         1.50 pounds         Coil Helix Direction:         Right-hand         Spring Price Outside Diameter:         0.212 inches         Hock Ratius:         0.212 inches         Mork Ratius:         0.213 inches         Spring Free Outside Diameter:         0.213 inches         Surface Treatment:         Tin         Stell         Surface Treatment:         Ini         Syle Designator:         Cylindrical         Sheft Life:         Na         Dird Measure:         Image:	Opening Width:
Machined half loop both ends         Spring Free Length:         0.927 inches         Coil Quantity:         26         Design Type:         Closed         Load Rating:         1.50 pounds         Coil Helix Direction:         Right-hand         Spring Deflection Rate:         3.200 pounds per inch         Spring Tree Outside Diameter:         0.212 inches         Hook Radius:         0.404 rinches         Spring Length Under Load:         1.343 inches         Marcinal:         Steel         Sufface Treatment:         Tin         Syle Designator:         Cylindrical         Sheft Life:         Na         Tord Measure:         Tord         Fig:	0.031 inches both ends
Spring Free Length:         0.927 inches         Coil Quantity:         28         Design Type:         Closed         Load Rating:         1.50 pounds         Coil Ulist Direction:         Right-hand         Spring Deflection Rate:         3.200 pounds per inch         Spring Free Outside Diameter:         0.212 inches         Hock Radius:         0.247 inches both ends         Spring Length Under Load:         1.343 inches         Material:         Steel         Surface Treatment:         Tin         Syle Designator:         Quintical         Sherie         Na         Ini Of Measure:         To         Spind Treatment:         Na         Ini Of Measure:         To         Spind Coll Second	End Style:
0.927 inchesCoil Quantity:26Design Type:ClosedLoad Rating:1.50 poundsCoil Helix Direction:Right-handSpring Deflection Rate:3.200 pounds per inchSpring Free Outside Diameter:0.212 inchesHock Radius:0.047 inches both endsSpring Length Under Load:1.343 inchesMaterial:SteelSurface Treatment:TinSyle Designator:CylindricalNaInd Measure:rNaFine:NaFine:NaPanilitarization:NoFine:NaFine:NaPanilitarization:NaFine:NaFine:NaPanilitarization:NaFine:NaPanilitarization:NaPanilitarization:NaPanilitarization:NaPanilitarization:NaPanilitarization:NaPanilitarization:NaPanilitarization:NaPanilitarization:Panilitarization:Panilitarization:Panilitarization:Panilitarization:Panilitarization:Panilitarization:Panilitarization:Panilitarization:Panilitarization:Panilita	Machined half loop both ends
Coil Quantity:26Posign Type:ClosedLoad Rating:1.50 poundsCoil Helix Direction:Right-handSpring Deflection Rate:3.200 pounds per inchSpring Free Outside Diameter:0.212 inchesHook Radius:0.404 rinches both endsSpring Length Under Load:1.343 inchesMaterial:SteelSurface Treatment:TinSyle Designator:CylindricalShelf Life:NaUnit of Measure:TuFinShelf Life:NaDint of Measure:TuFinSurface Treatment:NaDint of Measure:TuFinSteelSteelSteelSurface Treatment:NaSteel <tr< th=""><th>Spring Free Length:</th></tr<>	Spring Free Length:
26 <b>Pasign Type:</b> Closed <b>Lad Rating:</b> 1.50 pounds <b>Coil Helix Direction:</b> Right-hand <b>Spring Deflection Rate:</b> 3.200 pounds per inch         Spring Free Outside Diameter:         0.212 inches <b>Hock Radius:</b> 0.212 inches <b>Hock Radius:</b> 0.404 rinches both ends <b>Spring Length Under Load:</b> 1.343 inches <b>Material:</b> Steel <b>Surface Treatment:</b> Tin <b>Surface Treatment:</b> Quindriad         Shelf Life:         Na <b>Dirt of Measure:</b> Tr <b>Find Information:</b> Na <b>Dirt of Measure:</b> Tr <b>Panilitarization:</b> Na	0.927 inches
Design Type:ClosedLoad Rating:1.50 poundsCoil Helix Direction:Right-handSpring Deflection Rate:3.200 pounds per inchSpring Free Outside Diameter:0.212 inchesHook Radius:0.047 inches both endsSpring Length Under Load:1.343 inchesMaterial:SteelSurface Treatment:CylindricalSyle Designator:CylindricalInSuff Life:NaPinel Life:NaFine:Pinel Suff CollFine:NaFine:NaFine:NaFine:NaSufficie:NaSufficie:NaSufficie:NaSufficie: <tr< th=""><th>Coil Quantity:</th></tr<>	Coil Quantity:
Closed         Load Rating:         1.50 pounds         Coil Helix Direction:         Right-hand         Spring Deflection Rate:         3.200 pounds per inch         Spring Free Outside Diameter:         0.212 inches         Hook Radius:         0.471 inches both ends         Spring Length Under Load:         1.343 inches         Material:         Steel         Surface Treatment:         Tin         Syle Designator:         Cylindrical         Interface         Interface         Point Condeasure:         Interface         SurfaceTreatment:         Interface         Surfacial         Point Condeasure:         Interface         Fig:	26
Load Rating:1.50 poundsCoil Helix Direction:Right-handSpring Deflection Rate:3.200 pounds per inchDuring Free Outside Diameter:0.212 inchesHook Radius:0.212 inches both endsSpring Length Under Load:1.343 inchesMaterial:SteelSurface Treatment:TinStyle Designator:CylindricalShelf Life:NaInt of Measure:TinShelf Life:NaFig:Intiltarization:NoFig:	Design Type:
1.50 poundsCoil Helix Direction:Right-handSpring Deflection Rate:3.200 pounds per inchSpring Free Outside Diameter:0.212 inchesHook Radius:0.212 inchesJourface both endsSpring Length Under Load:1.343 inchesMaterial:SteelStrelStyle Designator:CylindricalShelf Life:NaDint of Measure:InShelf Life:NaFig:Stel	Closed
Coil Helix Direction:Right-handSpring Deflection Rate:3.200 pounds per inchSpring Free Outside Diameter:0.212 inchesHook Radius:0.047 inches both endsSpring Length Under Load:1.343 inchesMaterial:SteelSurface Treatment:CylindricalShelf Life:NaDidf Coll Measure:InShelf Life:NaFig:Sing Length Under Load:Shelf Life:Shelf Life:NaFig:Station:<	Load Rating:
Right-hand         Spring Deflection Rate:         3.200 pounds per inch         Spring Free Outside Diameter:         0.212 inches         Hook Radius:         0.047 inches both ends         Spring Length Under Load:         1.343 inches         Material:         Steel         Surface Treatment:         Tin         Style Designator:         Cylindrical         Shelf Life:         Na         Did Measure:         -         Ponilitarization:         No         Fig:	1.50 pounds
Spring Deflection Rate:         3.200 pounds per inch         Spring Free Outside Diameter:         0.212 inches         Hook Radius:         0.047 inches both ends         Spring Length Under Load:         1.343 inches         Material:         Steel         Surface Treatment:         Tin         Style Designator:         Cylindrical         Shelf Life:         N/a         Din Of Measure:         -         Pemilitarization:         No         Fig:	Coil Helix Direction:
3.200 pounds per inch Spring Free Outside Diameter: 0.212 inches Hook Radius: 0.047 inches both ends Spring Length Under Load: 1.343 inches Material: Steel Steel Surface Treatment: Tin Style Designator: Cylindrical Sheff Life: N/a Unit Of Measure: - Demilitarization: No	Right-hand
Spring Free Outside Diameter:0.212 inchesHook Radius:0.047 inches both endsSpring Length Under Load:1.343 inchesMaterial:SteelStrince Treatment:TinStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:NoFiig:	Spring Deflection Rate:
0.212 inches O.212 inches O.212 inches O.207 inches both ends Spring Length Under Load: I.343 inches Material: Steel Steel Streatment: Tin Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	3.200 pounds per inch
Hook Radius:0.047 inches both endsSpring Length Under Load:1.343 inches1.343 inchesMaterial:SteelSurface Treatment:TinStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Spring Free Outside Diameter:
0.047 inches both ends Spring Length Under Load: 1.343 inches Material: Steel Streatment: Tin Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	0.212 inches
Spring Length Under Load:1.343 inchesMaterial:SteelSurface Treatment:TinStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Hook Radius:
1.343 inches Material: Steel Surface Treatment: Tin Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.047 inches both ends
Material:SteelSurface Treatment:TinStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Penilitarization:NoFig:	Spring Length Under Load:
SteelSurface Treatment:TinStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	1.343 inches
Surface Treatment:TinStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:
TinStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Steel
Style Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Surface Treatment:
Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tin
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Style Designator:
N/a Unit Of Measure:  Demilitarization: No Fiig:	Cylindrical
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A02900	Fiig:
	A02900