NSN 5360-00-168-6953

Extension Helical Spring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5360-00-168-6953

insite function: Opening Widt: O251 Inches both ends End Style: Adathine loop both ends Stock Diameter: 0.062 Inches Socie Datates: O202 Inches Spring Fee Length: Ad50 Inches both ends Coil Quantity: Ad5 Design Type: Coil Quantity: Coil Quantity: Coil Quantity: Coil Quan	Inside Dismeter
Spening With: 0.500 inches both ends End Syle: Machine loop both ends Stock Diameter: 0.602 inches 0.602 inches Stock Diameter: 0.602 inches Stock Diameter: 0.602 inches Stock Diameter: 0.610 Quantity: 4.550 inches Bergin Type: Clock addity: Between 8.65 apounds and 44.77 pounds Between 8.65 apounds and 44.77 pounds Spring Free Outside Diameter: 1.5.000 pounds per inch 5.010 houts both ends End Angular Relationship: 1.5.010 pounds <	Inside Diameter:
0.0 inches both ends End Syle: Machine loop both ends Stock Diameter: 0.62 inches Spring Free Length: 4.65 inches Coll Quantity: 4.66 inches Design Type: Coll Quantity: Berley BS d5 pounds and 41.77 pounds Coll Helix Direction: Right-hand or left-hand Spring Free Outside Diameter: 0.520 jounds per inch Spring Free Outside Diameter: 0.375 inches Hold Radius: 0.300 inches both ends End Aguide Rolationship: End Aguider Rolationship: End Aguider Rolationship: 0.300 inches both ends Spring Length Under Load: 0.300 inches both ends	
Ext Style: Machine loop both ends Stock Diameter: 0.062 Inches Sching Free Length: 4.560 Inches Coll Quantity: 4.6 Design Type: Collaced Locad Rating: Between 36.63 pounds and 44.77 pounds Coll Quantity: Joing Tree Constit Styling Free Outside Diameter: Notify Tree Outside Diameter: 0.375 Inches Hook Radius: 0.376 Inches End Angular Relationship: 0.376 Inches Paring Tree Outside Diameter: 0.376 Inches Book Radius: 0.376 Inches String Tree Outside Diameter: 0.376 Inches Book Radius: 0.376 Inches Book Radius: 0.376 Inches Book Radius: 0.370 Inches Inches Book Radiuse Longthet	
Machine loop both ends Stock Diameter: 0.052 Indes Spring Free Length: 4.650 Indens Coll Quantity: 46 Design Type: Coll Quantity: Parse Antion	
Stock Diameter:0.062 inchesSeping Free Length:4.550 inchesCoil Quantity:46Beigen Type:Clock Coil Coil Coil Coil Coil Coil Coil Coil	
0.062 inchesSpring Free Length:4.650 inchesColloantity:46Besign Type:ClosedLoar Rating:Between 36.63 pounds and 44.77 poundsCollethix Direction:Right-hand or left-handSpring Deflection Rate:15.600 pounds per inchSpring Deflection Rate:0.375 inchesHork Radius:0.375 inchesHork Radius:0.300 inches both endsSpring Deflection Rate:0.300 inches lot enderBoring Length Under Load:8.570 inchesMarcial Specification:0.350 inches lot enderSpring Deflection Rate:0.350 inches lot enderBoring Length Under Load:0.350 inches lot ender0.350 inches lot ender <td></td>	
Spring Free Length: 4.650 inches Coll Quantity: 46 Besign Type: Closed Lead Rating: Between 36.63 pounds and 44.77 pounds Coll Hellx Direction: Righ-hand or left-hand Spring Deflection Rate: 15.600 pounds per inch Spring Free Outside Diameter: 0.375 inches Hock Radius: 0.375 inches Hock Radius: 0.301 inches both ends End Angular Relationship: Ends Angular Relationship: Ends Angular Relationship: 0.350 inches both ends Spring Length Under Load: 0.350 inches both ends Beter uns Ko8500 Material: 0.340 on to didram Isegnification single material response Surface Treatment Specification: 0.404 romate Surface Treatment Specification: 0.404 romate Surface Treatment Specification single treatment response Surface Treatment Specification single treatment response Surface Treatment Specification single treatment response Surface Treatment Specification sing	
4500 inclusts Coll Quantity: 46 Design Type: Closed Load Rating: Between 36.83 pounds and 44.77 pounds Coll Helix Direction: Right-hand or left-hand Spring Deflection Rate: 15.600 pounds per inch Spring Tree Outside Diameter: 0.375 inches Hock Radius: 0.130 inches both ends End Angular Relationship: Ends angled one to other Spring Length Under Load: 6.970 inches Coll To Hook Inside Length: 0.850 inches both ends Enders angled one to other Spring Length Under Load: 6.970 inches Coll To Hook Inside Length: 0.850 inches both ends Material Steel uns ko8500 Material Specification: Quary.000 id mare Indecidication single material response Surface Treatment Cadmium and chromate Surface Treatment Specification: Quap-416, type 2, class 3 federal specification single treatment response Surface Treatment Specification: Cadmi	
Coll Quantiy: 46 Design Type: Closed Closed Load Rating: Betwen 36.63 pounds and 44.77 pounds Coll Heix Direction: Right-hand or left-hand Spring Deflection Rate: 15.600 pounds per inch Spring Free Outside Diameter: 0.375 inches Hock Radlus: 0.375 inches Hock Radlus: 0.376 inches Find perfet Load Byring Free Outside Diameter: 0.375 inches Hock Radlus: 0.376 inches Find sangled one to other Spring Length Under Load: 6.370 inches Coll To Hock Inside Length: 0.350 inches both ends Materia! Stel uns ko8500 Materia! Q-w-470, cold drawn federal specification single material response Surface Treatment Cadmium and chromate Garp-p-16, kpe 2, class 3 federal specification single treatment response Surface Treatment Specification Cad-p-416, kpe 2, class 3 federal specification single treatment response	
46 Design Type: Closed Lead Rating: Between 36.83 pounds and 44.77 pounds Coll Hix Direction: Right-hand of left-hand Spring Oeffection Rate: 15.600 pounds per inch Spring Free Outside Diameter: 0.375 inches Hock Radius: 0.375 inches Forda Rationship: 1.30 inches both ends Parige Legtdon Index 6.370 inches Point Both Code: 6.370 inches Define Longth: 0.380 inches both ends Spring Length Under Load: 6.370 inches Define South ends Materia! 0.380 inches both ends Materia! 0.390 inches both ends 0.390 inches both ends 0.390 inc	
Pesign Type:ClosedLoad Rating:Between 36.63 pounds and 44.77 poundsCoil Helix Direction:Right-hand or left-handSpring Deflection Rate:15.600 pounds per inchSpring Free Outside Diameter:0.375 inchesHook Radius:0.130 inches both endsEnd Angular Relationship:Ends angled one to otherSpring Length Under Load:0.701 inchesOil To Hook Inside Length:0.800 inches both endsMaterialQuery Arq, cold drawn federal specification single material responseSurface TreatmentCadmiur and chomateSurface Treatment Specification:Q-ap-416, type 2, class 3 federal specification single treatment responseSurface TreatmentChargen Cali Specification:Outp-Deflection:Cadmiur and chomateSurface Treatment Specification:CadrolexDerp-416, type 2, class 3 federal specification single treatment responseSurface Treatment Specification:Chargen Cali Specification:CadrolexSurface Treatment Specification: <tr< td=""><td>Coil Quantity:</td></tr<>	Coil Quantity:
Closed Load Rating: Between 36.63 pounds and 44.77 pounds Coil Helix Direction: Right-hand or left-hand Spring Deflection Rate: 15.600 pounds per inch Spring Free Outside Diameter: 0.375 inches Hook Radius: 0.130 inches both ends End Angular Relationship: Ends angled one to other Spring Length Under Load: 6.970 inches Dot Hook Inside Length: 0.380 inches both ends Barcel Coll To Hook Inside Length: 0.850 inches both ends Material: 0.850 inches both ends Material 0.850 inches both ends Material 0.800 inches both ends Material 0.800 inches both ends Material 0.800 inches both ends Material 0.900 inches both ends Material 0.800 inches both ends Material 0.800 inches both ends Material 0.900 inches Material <	
Load Rating: Between 36:63 pounds and 44.77 pounds Coil Helix Direction: Right-hand or left-hand Spring Deflection Rate: 15:600 pounds per inch Spring Free Outside Diameter: 0.375 inches Hock Radius: 0.130 inches both ends End Angular Relationship: End Angular Relationship: 6.970 inches Oth To Hock Inside Length: 0.350 inches both ends Borgen Length Under Load: 6.970 inches Coll To Hock Inside Length: 0.3850 inches both ends Material: Quev-470, cold drawn federal specification single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification Quev-416, type 2, class 3 federal specification single treatment response Surface Treatment Specification Quev-416, type 2, class 3 federal specification single treatment response	
Between 36.63 pounds and 44.77 pounds Coil Helix Direction: Right-hand or left-hand Spring Deflection Rate: 15.600 pounds per inch Spring Free Outside Diameter: 0.375 inches Hook Radius: 0.130 inches both ends End Angular Relationship: Ends angled one to other Spring Length Under Load: 6.970 inches Coil To Hook Inside Length: 0.850 inches both ends Material Query 470, cold drawn federal specification single material response Surface Treatment Cadmium and chromate Surface Treatment Specification: Query-416, type 2, class 3 federal specification single treatment response Surface Treatment Specification single treatment response <td></td>	
Coil Heix Direction:Right-hand or left-handSpring Deflection Rate:15.600 pounds per inchSpring Free Outside Diameter:0.375 inchesHook Radius:0.130 inches both endsEnd Angular Relationship:Ends angled one to otherSpring Length Under Load:6.970 inchesCoil To Hook Inside Length:0.850 inches both endsMaterial:Query-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Query-416, type 2, class 3 federal specification single treatment responseSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseSurface Treatment Specification Specif	
Right-hand or left-hand Spring Deflection Rate: 15.600 pounds per inch Spring Free Outside Diameter: 0.375 inches Hock Radius: 0.130 inches both ends End Angular Relationship: Ends angled one to other Spring Length Under Load: 6.970 inches Coil To Hook Inside Length: 0.350 inches both ends Material: Stel uns k08500 Material Specification: 0.q-w-470, cold drawn federal specification single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: 0.q-p-416, type 2, class 3 federal specification single treatment response Surface Treatment: Cadmium and chromate	
Spring Deflection Rate:15.600 pounds per inchSpring Free Outside Diameter:0.375 inchesHook Radius:0.130 inches both endsChad Relationship:Ends angled one to otherSpring Length Under Load:6.970 inchesCoil To Hook Inside Length:0.380 inches both endsMaterial:Steel uns k08500Material Specification:Q-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateAufore Areation Specification:Q-p-416, type 2, class 3 federal specification single treatment responseSpie Designator:	Coil Helix Direction:
15.00 pounds per inch Spring Free Outside Diameter: 0.375 inches Hook Radius: 0.130 inches both ends End Angular Relationship: Ends angled one to other Spring Length Under Load: 6.970 inches Coil To Hook Inside Length: 0.380 inches both ends Material: Steil uns k08500 Material Specification: Qr-w-470, cold drawn federal specification single material response Surface Treatment: Cadmium and chromate Qr-p-416, type 2, class 3 federal specification single treatment response Style Designator:	Right-hand or left-hand
Spring Free Outside Diameter:0.375 inchesHook Radius:O.130 inches both endsChangular Relationship:End Angular Relationship:Ends angled one to otherSpring Length Under Load:6.970 inchesCoil To Hook Inside Length:0.850 inches both endsMaterial:Steel uns k08500Material Specification:Q-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateQ-p-416, type 2, class 3 federal specification single treatment responseSyle Designator:	Spring Deflection Rate:
0.375 inchesHook Radius:0.130 inches both endsEnd Angular Relationship:End Angular Relationship:Ends angled one to otherSpring Length Under Load:6.970 inchesCoil To Hook Inside Length:0.850 inches both endsMaterial:Steel uns k08500Material Specification:Q-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateQ-p-416, type 2, class 3 federal specification single treatment responseSyle Designator:	15.600 pounds per inch
Hock Radius:0.130 inches both endsEnd Angular Relationship:Ends angled one to otherSpring Length Under Load:6.970 inchesCoil To Hock Inside Length:0.850 inches both endsMaterial:Steel uns k08500Material Specification:Q-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Q-p-416, type 2, class 3 federal specification single treatment responseSyle Designator:	Spring Free Outside Diameter:
0.130 inches both endsEnd Angular Relationship:Ends angled one to otherSpring Length Under Load:6.970 inchesCoil To Hook Inside Length:0.850 inches both endsMaterial:Steel uns k08500Material Specification:Q-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Q-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	0.375 inches
End Angular Relationship:Ends angled one to otherSpring Length Under Load:6.970 inchesCoil To Hook Inside Length:0.850 inches both endsMaterial:Steel uns k08500Material Specification:Q-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateQu-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	Hook Radius:
Ends angled one to other Spring Length Under Load: 6.970 inches Coil To Hook Inside Length: 0.850 inches both ends Material: Steel uns k08500 Material Specification: Qq-w-470, cold drawn federal specification single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Style Designator:	0.130 inches both ends
Spring Length Under Load:6.970 inchesCoil To Hook Inside Length:0.850 inches both endsMaterial:Steel uns k08500Material Specification:Qq-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	End Angular Relationship:
6.970 inches Coil To Hook Inside Length: 0.850 inches both ends Material: Steel uns k08500 Material Specification: Qq-w-470, cold drawn federal specification single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Style Designator:	Ends angled one to other
Coil To Hook Inside Length:0.850 inches both endsMaterial:Steel uns k08500Material Specification:Qq-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	Spring Length Under Load:
0.850 inches both ends Material: Steel uns k08500 Material Specification: Qq-w-470, cold drawn federal specification single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Style Designator:	6.970 inches
Material:Steel uns k08500Material Specification:Qq-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	Coil To Hook Inside Length:
Steel uns k08500Material Specification:Qq-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	0.850 inches both ends
Material Specification:Qq-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	Material:
Qq-w-470, cold drawn federal specification single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, class 3 federal specification single treatment responseStyle Designator:	Steel uns k08500
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Style Designator:	Material Specification:
Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Style Designator:	Qq-w-470, cold drawn federal specification single material response
Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Style Designator:	Surface Treatment:
Qq-p-416, type 2, class 3 federal specification single treatment response Style Designator:	Cadmium and chromate
Style Designator:	Surface Treatment Specification:
	Qq-p-416, type 2, class 3 federal specification single treatment response
Cylindrical	Style Designator:
	Cylindrical
Shelf Life:	Shelf Life:
	N/a
	IV/a

NSN 5360-00-168-6953

Extension Helical Spring - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A02900