NSN 5360-00-432-3132

Extension Helical Spring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5360-00-432-3132

Inside Diameter: OBS inches OBS inches ODS inches ODS inches ODS Inches ODS Inches ODS Inches End Style: Machined half loop both ends Spring Free Length: ODS Inches Coll Quantity: Coll Quantity: Coll Quantity: Colsed Coll Adding: Coll Adding: Coll Halts Direction: Left-hand Spring Free Outside Diameter: ODS Inches ODS Inches Spring Length Under Load: ODS Inches Stell Surface Treatment: Passivate Style Designator: Cylindrical Sheft Life: Na
Opening Width:0.031 inches both endsEnd Style:Machined half loop both endsSpring Free Length:0.415 inchesCoil Quantity:12Design Type:ClosedLoad Rating:2.00 poundsCoil Heix Direction:Left-handSpring Free Outside Diameter:0.435 inchesHook Radius:0.430 inches both endsSpring Length Under Load:0.500 inchesMaterial:Stainless steelSyle Designator:CylindricalSheft Life:NaInt of Measure:-NaFing:NaFing:NaSpring ComplexitySpring Length Onder Load:Spring Length Under Load:Spring Length
0.031 inches both ends End Style: Machined half loop both ends Spring Free Length: 0.415 inches Coil Quantity: 12 Design Type: Closed Load Rating: 2.00 pounds Coil Heix Direction: Left-hand Spring Free Outside Diameter: 0.425 inches Hook Radius: 0.043 inches both ends Spring Length Under Load: 0.500 inches Material: Stainless steel Syle Designator: Cylindrical Shelf Life: N/a Unit Of Measure: - Temilitarization: No Fig:
End Style: Machined half loop both ends Spring Free Length: 0.415 inches Coil Quantity: 12 Design Type: Closed Lead Rating: 2.00 pounds Coil Helix Direction: Left-hand Spring Free Outside Diameter: 0.125 inches Hock Radius: 0.500 inches Spring Length Under Load: 0.500 inches Sufface Treatment: Passivate Syle Sufface Treatment: Passivate Style Designator: Na Fig:
Machined half loop both ends Spring Free Length: 0.415 inches Coil Quantity: 12 Design Type: Closed Load Rating: 2.00 pounds Coil Helix Direction: Left-hand Spring Free Outside Diameter: 0.125 inches Hock Radius: 0.031 inches both ends Spring Length Under Load: 0.500 inches Material: Stainless steel Sufface Treatment: Passivate Style Designator: Cylindrical Style Designator: N/a Init Of Measure: Demilitarization: No
Spring Free Length:0.415 inchesCoil Quantity:12Design Type:ClosedLoad Rating:2.00 poundsCoil Helix Direction:Left-handSpring Free Outside Diameter:0.125 inchesHock Radius:0.043 inches both endsSpring Length Under Load:0.500 inchesMaterial:Stainless steelSurface Treatment:PassivateSyle Designator:CylindricalSheff Life:NaInit of Measure:NoFig:
0.415 inchesCoil Quantity:12Design Type:ClosedLoad Rating:2.00 poundsCoil Helix Direction:Left-handSpring Free Outside Diameter:0.125 inchesHook Radius:0.043 inches both endsSpring Length Under Load:0.500 inchesMaterial:Stainless steelSurface Treatment:PassivateSyle Designator:CylindricalSheff Life:N/aDinti of Measure:-NoFig:
Coil Quantity:12Design Type:ClosedLoad Rating:2.00 poundsCoil Helix Direction:Left-handSpring Free Outside Diameter:0.125 inchesHock Radius:0.43 inches both endsSpring Length Under Load:0.500 inchesMaterial:Stainless steelSurface Treatment:PassivateSyle Designator:CylindricalShelf Life:NaUnit Of Measure:-Demilitarization:NoFig:
12 Design Type: Closed Load Rating: 2.00 pounds Coil Helix Direction: Left-hand Spring Free Outside Diameter: 0.125 inches Hock Radius: 0.043 inches both ends Spring Length Under Load: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Style Designator: Cylindrical Shelf Life: Na Dit Of Measure: - Demilitarization: No Fig:
Design Type:ClosedLoad Rating:2.00 poundsCoil Helix Direction:Left-handSpring Free Outside Diameter:0.125 inchesHook Radius:0.043 inches both endsSpring Length Under Load:0.500 inchesMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:CylindricalShelf Life:NaDin Constantion:NaFig:NoFig:
Closed Load Rating: 2.00 pounds Coll Helix Direction: Left-hand Spring Free Outside Diameter: 0.125 inches Hook Radius: 0.043 inches both ends Spring Length Under Load: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Style Designator: Cylindrical Shelf Life: Na Int of Measure: Demiltarization: No Fig:
Load Rating: 2.00 pounds Coil Helix Direction: Left-hand Spring Free Outside Diameter: 0.125 inches Hook Radius: 0.125 inches Hook Radius: 0.125 inches Moder Load: 0.043 inches both ends Spring Length Under Load: 0.500 inches Material: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
2.00 pounds Coil Helix Direction: Left-hand Spring Free Outside Diameter: 0.125 inches Hook Radius: 0.043 inches both ends Spring Length Under Load: 0.500 inches Material: 0.500 inches Material: Stainless steel Stainless steel Striface Treatment: Passivate Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Coil Helix Direction:Left-handSpring Free Outside Diameter:0.125 inchesHook Radius:0.043 inches both endsSpring Length Under Load:0.500 inchesMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:CylindricalShelf Life:N/aInt Of Measure:-Panilitarization:NoFiig:
Left-hand Spring Free Outside Diameter: 0.125 inches Hook Radius: 0.043 inches both ends Spring Length Under Load: 0.500 inches Material: Stainless steel Surface Treatment: Passivate Style Designator: Cylindrical Sheff Life: N/a Init Of Measure: Fmilitarization: No Fig:
Spring Free Outside Diameter:0.125 inchesHook Radius:0.043 inches both endsSpring Length Under Load:0.500 inchesMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:CylindricalSheff Life:N/aUnit Of Measure:-Demilitarization:NoFig:
0.125 inches Hook Radius: 0.043 inches both ends Spring Length Under Load: 0.500 inches Material: Stainless steel Stainless steel Surface Treatment: Passivate Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:
Hook Radius:0.043 inches both endsSpring Length Under Load:0.500 inchesMaterial:0.500 inchesMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:
0.043 inches both ends Spring Length Under Load: 0.500 inches Material: Stainless steel Stainless steel Surface Treatment: Passivate Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Fig:
Spring Length Under Load:0.500 inchesMaterial:Material:Stainless steelSurface Treatment:PassivateStyle Designator:CylindricalShelf Life:N/aDemilitarization:NoFig:
0.500 inches Material: Stainless steel Surface Treatment: Passivate Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Fig:
Material:Stainless steelSurface Treatment:PassivatePassivateStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:
Stainless steel Surface Treatment: Passivate Passivate Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:
Surface Treatment:PassivateStyle Designator:CylindricalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:
Passivate Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:
Style Designator: Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Cylindrical Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
N/a Unit Of Measure: Demilitarization: No Fiig:
Unit Of Measure: Demilitarization: No Fiig:
 Demilitarization: No Fiig:
Demilitarization: No Fiig:
No Fiig:
Fiig:
A02900