NSN 5360-00-534-9932

Flat Spring - Page 1 of 1

A02900



View Online at https://aerobasegroup.com/nsn/5360-00-534-9932

End Application:
1005-672-1767
Special Features:
Usteel, prebent strip metal 1.250 in. W, 0.024 in. Thk, 1st end 1.250in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W, 2nd end 1.000 in. W tapers at 15 degrees angle to 1.250 in. W tapers at 15 degrees angle to 1.250 in. W tapers at 15 degrees angle to 1.250 in. W tapers at 15 degrees angle to 1.250 in. W tapers at 15 degrees at 15 degre
holesdrilled in 1st end 0.250 in. From end and 0.141 in. From sides, 0.992 in.O/a lg after shaping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: