Compression Helical Spring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5360-00-614-3698

Inside Diameter: 0.416 inches End Style: Spring end, squared and ground both ends Spring Free Length: 1.035 inches Coil Quantity: 6-1/2 Spring Solid Length: 0.436 inches Coil Helix Direction: Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment: Cadmium
End Style:Spring end, squared and ground both endsSpring Free Length:1.035 inchesCoil Quantity:6-1/2Spring Solid Length:0.436 inchesCoil Helix Direction:Right-handSpring Deflection Rate:55.000 pounds per inchSpring Free Outside Diameter:Between 0.540 inches and 0.550 inchesMaterial:SteelSurface Treatment:
Spring end, squared and ground both ends Spring Free Length: 1.035 inches Coil Quantity: 6-1/2 Spring Solid Length: 0.436 inches Coil Helix Direction: Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Spring Free Length:1.035 inchesCoil Quantity:6-1/2Spring Solid Length:0.436 inchesCoil Helix Direction:Right-handSpring Deflection Rate:55.000 pounds per inchSpring Free Outside Diameter:Between 0.540 inches and 0.550 inchesMaterial:SteelSurface Treatment:
1.035 inches Coil Quantity: 6-1/2 Spring Solid Length: 0.436 inches Coil Helix Direction: Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Coil Quantity: 6-1/2 Spring Solid Length: 0.436 inches Coil Helix Direction: Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
6-1/2 Spring Solid Length: 0.436 inches Coil Helix Direction: Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Spring Solid Length:0.436 inchesCoil Helix Direction:Right-handSpring Deflection Rate:55.000 pounds per inchSpring Free Outside Diameter:Between 0.540 inches and 0.550 inchesMaterial:SteelSurface Treatment:
0.436 inches Coil Helix Direction: Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Coil Helix Direction: Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Right-hand Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Spring Deflection Rate: 55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
55.000 pounds per inch Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Spring Free Outside Diameter: Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Between 0.540 inches and 0.550 inches Material: Steel Surface Treatment:
Material: Steel Surface Treatment:
Steel Surface Treatment:
Surface Treatment:
Cadmium
Style Designator:
Cylindrical
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02900