## NSN 5365-00-012-4368

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-012-4368 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.145 inches and 0.155 inches **Overall Length:** Between 0.200 inches and 0.210 inches **Thread Size:** 1-5/8 in.-20 **Bore Diameter:** Between 0.417 inches and 0.432 inches Between 0.210 inches and 0.220 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Internal groove **Thread Location:** Both ends **Accommodation Type And Quantity:** Grooves2 Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Aluminum alloy, qq-a-225/4, t6 Material: Aluminum alloy 2014 **Surface Treatment:** Anodize

**Surface Treatment:** 

Anodized

## NSN 5365-00-012-4368

Externally Threaded Ring - Page 2 of 2



|  | Fsc | App | lication | Data: |
|--|-----|-----|----------|-------|
|--|-----|-----|----------|-------|

Engine, aircraft, turbo-prop

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d