Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-013-4411

9aTread Direction:Right-handCasehardening Indicator:Not casehardenedChamfer Angle In Deg:45.0Chamfer Length:0.030 inchesWith:0.030 inchesOverall Length:0.250 inchesThread Size:1/2 in .40Bore Diameter:0.344 inchesDepth:0.344 inchesDepth:0.394 inchesDirect Size:1/2 in .20Bree Diameter:0.344 inchesDepth:0.344 inchesDepth:0.344 inchesDirect Size:1/2 in .20Bree Size:1/2 in .20Direct Size:0.344 inchesDirect Size:1/2 in .20Direct Size:1/2 in .20Direct Size:1/2 in .20Direct Size:1/2 in .20Bree Size:1/2 in .20Direct Size:1/2 in .20Direct Size:1/2 in .20Direct Size:1/2 in .201/2 in .
Right-handCasehardening Indicator:Not casehardenedChamfer Angle In Deg:45.0Chamfer Length:0.030 inchesWidth:0.034 inchesOverall Length:0.205 inchesThread Size:1/2 in20Bore Diameter:0.344 inchesDepth:0.934 inchesDiregtingStraightCore Shape:StraightDire Thread Size:Dire Shape:Dire Shape:Dire Shape:StraightDire Thread Size:Dire Thread Size: <t< th=""></t<>
Casehardenig Indicator:Not casehardenedChamfer Angle In Deg:45.0Chamfer Length:0.030 inchesWidth:0.094 inchesOverall Length:0.250 inchesThread Size:1/2 in20Bore Diameter:0.344 inchesDepth:0.934 inchesBore Shape:StraightCrew Thread Steise Designator:UrfDrive Type:
Nt casehardenedChamfer Angle In Deg:45.0Chamfer Length:0.030 inchesWidth:0.094 inchesOverall Length:0.250 inchesThread Size:1/2 in . 20Bore Diameter:0.344 inchesDepth:0.094 inchesBoresStraightStraightCrew Thread Series Designator:UriDrive Type:
Chamfer Angle In Deg:45.0Chamfer Length:0.030 inchesWidth:0.094 inchesOureall Length:0.250 inchesThread Size:1/2 in . 20Bore Diameter:0.344 inchesDepth:0.094 inchesBoresStraightStraightStraightUriUriDire Type:
45.0Chamfer Length:0.030 inchesWidth:0.094 inchesOverall Length:0.250 inchesThread Size:1/2 in . 20Bore Diameter:0.344 inchesDepth:0.094 inchesStraightStraightStraightUniUniDive Type:
Chamfer Length:0.030 inchesWidth:0.094 inchesOverall Length:0.250 inchesThread Size:1/2 in - 20Bore Diameter:0.344 inchesDepth:0.994 inchesStraightStraightLingthUnfDive Type:
0.030 inchesWidth:0.094 inchesOverall Length:0.250 inchesThread Size:1/2 in - 20Bore Diameter:0.344 inchesDepth:0.994 inchesBore Shape:StraightStraightUnfDive Type:
Width:0.094 inchesOverall Length:0.250 inchesThread Size:1/2 in . 20Bore Diameter:0.344 inchesDepth:0.094 inchesBore Shape:StraightCrew Thread Series Designator:UnfDiver Type:
0.094 inches Overall Length: 0.250 inches Thread Size: 1/2 in - 20 Bore Diameter: 0.344 inches 0.344 inches Depth: 0.094 inches Bore Shape: Straight Straight Dire Thread Series Designator:
Overall Length:0.250 inches0.250 inchesThread Size:1/2 in . 20Bore Diameter:0.344 inchesDepth:0.094 inchesBore Shape:StraightScrew Thread Series Designator:UnfDive Type:
0.250 inches Thread Size: 1/2 in .20 Bore Diameter: 0.344 inches Depth: 0.094 inches Bore Shape: Straight Straight Unf Duf Dive Type:
Thread Size:1/2 in20Bore Diameter:0.344 inchesDepth:0.094 inchesBore Shape:StraightStrew Thread Series Designator:UnfDive Type:
1/2 in20Bore Diameter:0.344 inchesDepth:0.094 inchesBore Shape:StraightScrew Thread Series Designator:UnfDrive Type:
Bore Diameter:0.344 inchesDepth:0.094 inchesBore Shape:StraightStrew Thread Series Designator:UnfDrive Type:
0.344 inches Depth: 0.094 inches Bore Shape: Straight Screw Thread Series Designator: Unf Drive Type:
Depth:0.094 inchesBore Shape:StraightScrew Thread Series Designator:UnfDrive Type:
0.094 inches Bore Shape: Straight Screw Thread Series Designator: Unf Drive Type:
Bore Shape: Straight Screw Thread Series Designator: Unf Drive Type:
Straight Screw Thread Series Designator: Unf Drive Type:
Screw Thread Series Designator: Unf Drive Type:
Unf Drive Type:
Drive Type:
Slotted face
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
180.0 Beveled Thread:
Beveled Thread:
Beveled Thread: Not included
Beveled Thread: Not included Bore Annular Internal Serration:
Beveled Thread: Not included Bore Annular Internal Serration: Not included
Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch:
Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included
Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process:
Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedBore Edge Process:Chamfered
Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedBore Edge Process:ChamferedProcess End Location:

NSN 5365-00-013-4411

Externally Threaded Ring - Page 2 of 2

Material:

Copper alloy 172 or copper alloy 173

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d

