## NSN 5365-00-017-6178

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-017-6178 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.052 inches Width: 0.060 inches **Overall Length:** Between 0.273 inches and 0.279 inches **Thread Size:** 0.688-24 **Bore Diameter:** Between 0.417 inches and 0.432 inches Depth: Between 0.050 inches and 0.060 inches Bore Shape: Straight **Screw Thread Series Designator:** Unef **Drive Type:** Slotted face **Material Hardness Rating:** 78.0 rockwell b **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** 

Not included

Bore Annular Internal Serration:
Not included

Setscrew Locking Notch:
Not included

Bore Edge Process:
Chamfered

Process End Location:
Drive end

## NSN 5365-00-017-6178

Externally Threaded Ring - Page 2 of 2



M	lat	Or	וכו	

Aluminum alloy, ams 4121

Material:

Aluminum alloy, ams 4121

**Surface Treatment:** 

Chromate, mil-a-8625, type 1

**Surface Treatment:** 

Chromate, mil-a-8625, type 1

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d