## NSN 5365-00-019-6624

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-019-6624 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** Between 0.480 inches and 0.490 inches Diameter: Between 0.127 inches and 0.133 inches **Thread Size:** 1.562-18 **Bore Diameter:** Between 0.686 inches and 0.695 inches Depth: 0.190 inches Bore Shape: Straight **Screw Thread Series Designator:** Unef **Drive Type:** Drilled face **Thread Location:** Both ends **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.650 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Counterbore 1.1230 in. Min, 1.1240 in. Max, opposite of drive end Material:

Aluminum alloy, qq-a-225/9, alloy 7075, t651

Material:

Aluminum alloy 7075

## NSN 5365-00-019-6624

Externally Threaded Ring - Page 2 of 2



**Surface Treatment:** 

Anodize mil-a-8625 type 1

**Surface Treatment:** 

Anodize mil-a-8625 type 1

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d