## NSN 5365-00-020-5756

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-020-5756 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.045 inches Width: 0.875 inches **Overall Length:** 0.719 inches **Thread Size:** 0.9375-20 **Bore Diameter:** 0.500 inches Bore Shape: Straight **Screw Thread Series Designator:** Nef **Drive Type:** Milled wrenching flats **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** Flats2

Angle Between Accommodations In Deg: 180.0 **Radius From Geometric Axis To Accommodation:** 0.437 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** End opposite drive end

## **NSN 5365-00-020-5756**Externally Threaded Ring - Page 2 of 2



Material:
Steel, mil-s-6758, comp 4130, cond c
Material:
Steel comp 4130
Surface Treatment:
Cadmium
Surface Treatment:
Cadmium plated
Fsc Application Data:
Cap assembly end, nose landing gear
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d