## NSN 5365-00-026-9014

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-026-9014 **Thread Class:** За **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 20.0 **Chamfer Length:** 0.046 inches Width: 0.125 inches **Overall Length:** 0.343 inches **Taper Minor Diameter:** 1.128 inches **Taper Major Diameter:** 1.330 inches **Thread Size:** 1.562 in.-32 Depth: 0.125 inches Bore Shape: **Tapered Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 120.0 **Beveled Thread:** Not included **Taper Major Diameter Location:** Drive end **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included

Bore Edge Process:
Chamfered
Process End Location:
Drive end

## NSN 5365-00-026-9014

No **Fiig:** T252-d

Externally Threaded Ring - Page 2 of 2



| Special Features:  |
|--|
| Counter bore 1.437 in. Diameter by 0.200 in. Lg on end opposite to drive end |
| Material:  |
| Steel, mil-s-7720, cond a  |
| Material:  |
| Steel comp 302 or steel comp 316 or steel comp 303 or steel comp 303se       |
| Surface Treatment:   |
| Aluminum alloy   |
| Surface Treatment:   |
| Aluminized   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |