

View Online at <https://aerobasegroup.com/nsn/5365-00-053-1676>

**End Application:**

T-53 series engines

**General Description:**

Cres ams5645, rockwell a scale 46.6 min, 63 maximum hardness, 5.890 in. Nom o/a od, 0.560 in. Nom lg, 5.395 in. Min, 5.400 in. Maximum diameter hub, 0.130 in. Lg hub, 4.430 in. Diameter bore, 0.190 in. Min, 0.200 in. Maximum dp bore, 5.760 in. Min, 5.762 in. Maximum diameter counterbore, 0.290 in. Dp counterbore, 5.750 in. Min, 5.752 in. Maximum diameter inside groove, 0.070 in. Min, 0.080 in. Maximum lg inside groove, 8 holes 0.279 in. Min, 0.286 in. Maximum diameter located on 4.960 in. Diameter bolt circle, 3 holes 0.340 in. Min, 0.345 in. Maximum diameter counterbored 0.385 in. Min, 0.390 in. Maximum dia, 0.080 in. Dp located on 4.960 in. Diameter bolt circle 4 slots equally spaced in bore, 2 slots 0.860 in. W, 1 slot 0.900 in. W, 1 slot 0.640 in. W

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No