NSN 5365-00-056-1338

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-056-1338 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 60.0 **Chamfer Length:** 0.075 inches Width: 0.062 inches **Overall Length:** 0.375 inches **Thread Size:** 0.6875-24 **Bore Diameter:** Between 0.3438 inches and 0.3448 inches Depth: 0.062 inches **End Application:** Butterfly valve, p/n 4158-00 **Bore Shape:** Straight **Screw Thread Series Designator:** Unef **Drive Type:** Slotted face **Thread Location:** Drive end **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:**

Setscrew Locking No Not included Bore Edge Process: Chamfered

NSN 5365-00-056-1338

Externally Threaded Ring - Page 2 of 2



Process End Location:
Drive end
Material:
Carbon graphite
Material:
Graphite
Fsc Application Data:
Engine accessory, acft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d