

View Online at <https://aerobasegroup.com/nsn/5365-00-057-7146>

**Thread Pitch Diameters:**

+0.3546 to 0.3930 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.010 inches

**Overall Length:**

0.078 inches

**Diameter:**

0.031 inches

**Thread Size:**

0.393-32

**Bore Diameter:**

Between 0.188 inches and 0.193 inches

**Depth:**

0.078 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Drilled face

**Accommodation Type And Quantity:**

2 holes

**Angle Between Accommodations In Deg:**

180.0

**Radius From Geometric Axis To Accommodation:**

0.140 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Drive end

**Material:**

Aluminum alloy, qq-a-225/6, t4

**Material:**

Aluminum alloy 2024

**Surface Treatment:**

Anodize or anodize

**Surface Treatment:**

Anodized, mil-a-8625, type 1, class 2 or anodized, mil-a-8625, type 2, class 2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d