

View Online at <https://aerobasegroup.com/nsn/5365-00-071-1875>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Width:**

0.187 inches

**Overall Length:**

0.500 inches

**Thread Size:**

1.750-12

**Bore Diameter:**

1.165 inches

**Depth:**

0.250 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Material Hardness Rating:**

Between 35.0 rockwell c and 40.0 rockwell c

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Both ends

**Material:**

Steel, mil-s-5626

**Material:**

Steel comp 4140

**Surface Treatment:**

Cadmium

**Surface Treatment:**

Cadmium plated

**Fsc Application Data:**

Beam assembly, landing gear, acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d